



Range/dryer/car charger electrical box for use with nonmetallic sheathed cable

---

**Mounting Description:** Nail-on with fetter ring nails

---

**Box Type:** Wall - Switch/Receptacle

---

**Box Features:** Nails

---

**Installation Type:** New Work

---

**Height:** 3-3/4 in

---

**Width:** 4 in

---

**Depth:** 3-13/16 in

---

**Volume:** 42 cu in

## Product Info

**Brand:** Fiberglass

---

**Carton Weight:** 22 lbs

---

**Carton Length:** 22 in

---

**Carton Width:** 9 in

---

**Carton Height:** 13 in

---

**Country of Origin:** China

---

**Color:** Off white

---

**Material:** Fiberglass reinforced polyester

---

**Additional Materials:** Carbon steel fasteners, Plated carbon steel clamp and fasteners

**Features:** Machine tapped holes for 2-position device , internal metal clamp for easy wire adjustment, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

---

### Application:

New work residential construction 2 HR fire resistive walls

---

### Standards:

ANSI / UL 514C




---

### Fire Classification:

#### Fire Test of Building Construction Materials

ANSI / UL 263:

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches